


CALCO TER



✓ = standard ○ = optional

TECHNICAL FEATURES

COPY ROUTER UNIT

• Dual rotation speed spindle	12.000 rpm
• Tool coupling	ER 16
• Quick locking of the spindle to facilitate tool changing	✓
• Horizontal vices	2
• Jigs	2
• Retractable stops	2
• Vice jaw extension 805 mm (Rh and/or Lh)	○
• Side support surfaces 1800 mm (Rh and/or Lh)	○
• Ability to work with jigs or with mechanical stops	✓
• Independent pneumatic tracer with double diameter selector Ø 5 and Ø 8 mm	1
• Tool mist lubrication	✓
• Minimum lubrication with pure oil	○
• Air filter group	✓
• Supplementary retractable stop	○
• Supplementary retractable magnetic stop	○
• Change unit of measurement to inches	○

DRILLING UNIT

• Motor power	1,1 kW
• Number of chucks	3
• Double diameter bit Ø 6/12 mm shank Ø 10 mm	1
• Double diameter bit Ø 6/10 mm shank Ø 10 mm	2
• Distance between holes	22 mm
• Hydraulic unit feed	✓
• Bit rotation speed	900 rpm
• Boring unit height adjustment from 10 to 90 mm with manual handwheel assisted by decimal display	✓
• Transversal adjustment of the drilling unit with metric rod stroke 55 mm	✓