



# SUPER BROWN 2000 MRM

## MANUAL CIRCULAR SAW

### MACHINE COMPLETE WITH:

Manual vice with rapid clamping. - Safety switch for blade drive on lever hand grip. - Complete protection guard with rapid blade change system. - Emergency push button with key on control panel. - Two-speed switch. - Tilting head on adjustable self-lubricating bushings. - Mechanism for the rotation of head block for angled cuts up to 45° left and right with blocking lever. - Lateral head movement unit for 45° cuts left and longitudinal cuts. - Support crank which allows to cut with the same ease and performances big pieces (crank forward) and small pieces (crank back). - Refrigerating liquid tank with immersion pump to reduce overall dimensions. - Bar stop with millimetre ruler. - Circular blade  $\varnothing$  275. - Instruction book for use and maintenance. - Set keys for maintenance.

### SUPER BROWN 2000 MRM: MANUAL CIRCULAR SAW

2 speed three phase (V 230-50 o V 400-50)


### ACCESSORIES UPON REQUEST:

Micromist lubrication

Loading and unloading roller tables



45° cuts off the vertical



Sideways movement of the head for cuts at 45° on the vertical plane and for longitudinal cuts.

















Longitudinal cuts



### CUTTING CAPACITY

### TECHNICAL DATA

				
	45	0	45	60
 mm	80	80	80	-
 mm	65	80	70	-
 mm	70 x 65	100 x 70	75 x 70	-
 kW	1.6 / 2.0			
 RPM	43 / 86			
 mm	140			
 mm	300			
 kg	230			
 mm	550 x 1200 x 1800			
 mm	950			



Viale Pecori Giraldi, 51 - 36061 Bassano del Grappa (VI) | Tel.: (+39) 0424 50 90 11 | Mail: [info@pedrazzoli.ercolina.it](mailto:info@pedrazzoli.ercolina.it) | Web: [www.pedrazzoli.it](http://www.pedrazzoli.it)



# SUPER BROWN 2000 MRP

## MANUAL CIRCULAR SAW

### MACHINE COMPLETE WITH:

Pneumatic vice with rapid clamping. - Safety switch for blade drive on lever hand grip. - Complete protection guard with rapid blade change system. - Emergency push button with key on control panel. - Two-speed switch. - Tilting head on adjustable self-lubricating bushings. - Mechanism for the rotation of head block for angled cuts up to 45° left and right with blocking lever. - Lateral head movement unit for 45° cuts left and longitudinal cuts. - Support crank which allows to cut with the same ease and performances big pieces (crank forward) and small pieces (crank back). - Refrigerating liquid tank with immersion pump to reduce overall dimensions. - Bar stop with millimetre ruler. - Circular blade  $\varnothing$  275. - Instruction book for use and maintenance. - Set keys for maintenance.

### SUPER BROWN 2000 MRP: MANUAL CIRCULAR SAW WITH PNEUMATIC VICE

2 speed three phase (V 230-50 o V 400-50)


### ACCESSORIES UPON REQUEST:

Micromist lubrication

Loading and unloading roller tables



45° cuts off the vertical



Sideways movement of the head for cuts at 45° on the vertical plane and for longitudinal cuts.

















Longitudinal cuts



### CUTTING CAPACITY

### TECHNICAL DATA

				
 mm	80	80	80	-
 mm	65	80	70	-
 mm	70 x 65	100 x 70	75 x 70	-
 kW	1.6 / 2.0			
 RPM	43 / 86			
 mm	140			
 mm	300			
 kg	240			
 mm	550 x 1200 x 1800			
 mm	950			